



PUKEPINE
SAWMILLS

For all your
fencing we've got
you covered

pukepine.co.nz

Primewood fencing helps turn your outdoor dreams into reality.

Many homeowners appreciate the classic look and feel of traditional painted wood fence. Primewood fences add that traditional touch to a home, as well as providing privacy and security.

A solid privacy fence using the Shiplap or TGV profiles will add an extra touch of solitude to a home. This type of fence can also protect against harsh winds and distracting street noise.



Primewood machine finished palings represent a quality fencing option, they still have a classic, traditional appearance but they have a contemporary, smoother finish. The Primewood fencing range offer durability by combining a robust specification with quality materials that are supplied treated and primed ready for installation.

Posts and post capping are not part of the Primewood fencing solution and need to be purchased separately. However we recommend 90 x 90 or 112 x 112 H5 gauged posts to complete the premium look of your fence.

PRIMEWOOD FENCING — ALL COMPONENTS FJ H3.1 PREPRIMED

Description	Size (mm)
Primewood Tongue & Groove Paling	140 x 18 x 1800
Primewood Shiplap Paling	140 x 18 x 1800
Primewood Top Rail	90 x 42 x 5400
Primewood Middle Rail	90 x 38 x 5400
Primewood Bottom Rail	90 x 42 x 5400



Complimenting our Primewood Fencing we also supply...

New Zealand's traditional rough sawn 25mm fence palings. Ideally uses as a straight forward solution to complete the look of your landscaping, securing your property or just define your boundary.

ROUGH SAWN PALINGS & RAILS H3.2

Description	Size (mm)
Rough Sawn Paling	150 x 25 x 1200
Rough Sawn Paling	150 x 25 x 1500
Rough Sawn Paling	150 x 25 x 1800
Rough Sawn Paling	150 x 25 x 2100
Rough Sawn Paling	150 x 25 x 2400
Rough Sawn Rail	100 x 50 x 4800




H3.2 treated for the outdoors, they can be used to enhance your property, quickly adding something unique.

Our natural timber palings can be stained or left to weather naturally over time.

PREMIUM FENCING PALINGS H3.2

Description	Size (mm)
Premium Shiplap Paling	150 x 25 x 1800



Installation and Painting recommendations for Primewood fencing

All components are manufactured from H3.1 treated finger-jointed radiata pine and have been factory primed with an alkyd (oil based) primer.

Posts and post capping are not part of the Primewood fencing solution and need to be purchased separately. However we recommend 90 x 90 or 112 x 112 H5 gauged posts to complete the premium look of your fence.

Once the fence has been installed we recommend the paint finishing be completed with a minimum of two premium exterior top coats at an LRV of 45 or higher.

Disposal

Preserved wood may be disposed of in landfills, or burned in commercial or industrial incinerators or boilers, in accordance with local council rules and regulations.

Guidelines to assist with maximising the lifespan of your Primewood fence.

- 1 Bottom rail needs to be installed with suitable ground clearance to ensure surface water and soil is not in contact with rail.
- 2 If possible we recommend painting the bottom rail with a top coat before installing as proximity to the ground can make this difficult once in place.
- 3 Prime all cut ends and any exposed timber with a premium timber alkyd primer prior to installation.
- 4 All nail and screw holes should be filled with a suitable wood filler as soon as possible after creation to avoid unnecessary moisture ingress.
- 5 Before painting clean down fence to remove and dirt and surface contaminates. All initial coating and subsequent maintenance is to be done in accordance with the paint manufacturers instructions.

PUREPINE
MOULDINGS

PUKEPINE
SAWMILLS

pukepine.co.nz

